

HI-WALL



		42QHC009DS	42QHC012DS	42QHC018DS	42QHC024DS
Cooling capacity	kW	2,70	3,52	5,28	6,40
Heating capacity	kW	2,90	3,80	5,50	7,00
Sound power level	dB(A)	53	54	57	63
Sound pressure level (high/med/low/silence)	dB(A)	38/34/30/21	40/35/31/22	42/37/35/24	47/42/38/26
Air flow (high/med/low/silence)	m ³ /h	460/380/280/190	500/390/300/200	760/550/460/260	1150/890/770/420
Weight (net/gross)	kg	8.0 / 10.5	9.0 / 12.0	11.5 / 16.5	13.5 / 18.5
Dimensions (WxDxH)	mm	730x192x291	812x192x300	973x218x319	1082x225x338
Refrigerant piping (Liquid side/Gas side)	inch	1/4"/3/8"	1/4"/3/8"	1/4"/1/2"	3/8"/5/8"
Power supply	V-ph-Hz	220-240V~, 50/60Hz, 1Ph	220-240V~, 50/60Hz, 1Ph	220-240V~, 50/60Hz, 1Ph	220-240V~, 50/60Hz, 1Ph

CONSOLE



		42QZA009DS-I	42QZA012DS-I	42QZA018DS-I
Cooling capacity	kW	2,64	3,52	4,40
Heating capacity	kW	2,90	3,70	5,40
Sound power level	dB(A)	60	60	60
Sound pressure level (high/med/low)	dB(A)	43/39/34	45/43/38	46/44/42
Air flow (high/med/low)	m ³ /h	460/400/360	530/480/360	530/470/430
Weight (net/gross)	kg	13.5/18.0	15.0/19.5	15.0/19.5
Dimension (W*D*H)	mm	700x600x210	700x600x210	700x600x210
Refrigerant piping (Liquid side/Gas side)	inch	1/4"/3/8"	1/4"/3/8"	1/4"/1/2"
Power supply	V-ph-Hz	220-240V~, 50/60Hz, 1Ph	220-240V~, 50/60Hz, 1Ph	220-240V~, 50/60Hz, 1Ph

CASSETTE



		42QTD009DS-1	42QTD012DS-1	42QTD018DS-1	42QTD024DS-1
Cooling capacity	kW	2,64	3,52	5,00	7,03
Heating capacity	kW	3,00	4,00	5,50	7,03
Sound power level	dB(A)	58	59	60	61
Sound pressure level (high/med/low)	dB(A)	42/39/36	42/39/36	45/42/36	49/46/43
Air flow (high/med/low)	m ³ /h	560/430/390	560/430/390	650/530/370	1350/1200/1070
Weight (net/gross) (Body)	kg	15.0/18.0	16.5/19.0	16.5/19.0	24.5/30.0
Weight (net/gross) (Panel)	kg	2.5/4.5	2.5/4.5	2.5/4.5	5 / 8
Dimensions (WxDxH) (Body)	mm	570x570x260	570x570x260	570x570x260	840x840x245
Dimensions (WxDxH) (Panel)	mm	647x647x50	647x647x50	647x647x50	950x950x55
Refrigerant piping (Liquid side/Gas side)	inch	1/4"/3/8"	1/4"/3/8"	1/4"/1/2"	3/8"/5/8"
Power supply	V-ph-Hz	220-240V~, 50/60Hz, 1Ph	220-240V~, 50/60Hz, 1Ph	220-240V~, 50/60Hz, 1Ph	220-240V~, 50/60Hz, 1Ph

DUCTED



		42QSS009DS-1	42QSS012DS-1	42QSS018DS-1	42QSS024DS-1
Cooling capacity	kW	2,65	3,52	5,00	7,03
Heating capacity	kW	3,25	3,80	5,40	7,40
Sound power level	dB(A)	60	60	60	61
Sound pressure level (high/med/low)	dB(A)	42/38/35	42/38/35	42/40/38	43/40/38
Air flow (high/med/low)	m ³ /h	540/500/370	540/500/370	790/660/490	1120/900/420
Weight (net/gross)	kg	18.5/23.0	18.5/23.0	23.0/29.0	30.2/37.3
Dimensions (WxDxH)	mm	700x635x210	700x635x210	880x674x210	1100x774x249
Refrigerant piping (Liquid side/Gas side)	inch	1/4"/3/8"	1/4"/3/8"	1/4"/1/2"	3/8"/5/8"
Power supply	V-ph-Hz	220-240V~, 50/60Hz, 1Ph	220-240V~, 50/60Hz, 1Ph	220-240V~, 50/60Hz, 1Ph	220-240V~, 50/60Hz, 1Ph

H/M/L/SL: High / Medium / Low / Super Low
WxDxH: Width x Depth x Height